SALES SUPPORT / ADMIN FABRIKSPARKEN 13 DK-2600 GLOSTRUP +45 36 72 75 00 SALES@SOROTO.DK

SOROTO@SOROTO.DK WWW.SOROTO.DK



300 L MIXER





Item no. 300 024B

SOROTO

300L-30

Mixer arms, complete set incl. rubber blades, top disc, U-bolts Item no. 300 024

Mixer arms wo/top disc, wo/rubber blades



TURBO mixer arm wo/rubber blades Item no. 300 025



Ball coupling for the towbar Item no. 300 018

SOROTO

The SoRoTo's 300 L mixer is one of the two models supplied with 400V and designed for larger assignments - and still it is easy to move around on the job site or from one job site to another, due of the towbar

CE

GB-12 10 17

The mixer can be towed behind a car with the removable tow-hook. It is equipped with three removable wheels. This makes it easy to move around a building site.

As an extra bonus for large building sites, this model is equipped with three lifting rings, so that it can be transported by crane.

It is equipped with and additional 230V outlet for supplying power to e.g. a vacuum cleaner, lighting or to a belt conveyor system.

The best mix is obtained in just 3-5 min.

The mixer arms may be removed without any use of tools if additional space for e.g. cleaning the mixer is required.

The mixer arms may be replaced individually.

It is possible to change between rubber blandes and Hardox steel blades according to the mixture needed for the current job.

The 300 L mixer is also equipped with telescopic legs and may easily be adjusted to the best possible working height for the person operating the mixer at any time.

Item no. 300 000 (with rubber blades as standard)

300L*
400
3.0
30
300
270
120-140
100/120
281



Mixer blades, rubber, Item no. 300 024R



Mixer blades, Hardoxsteel Item no. 300 024S



Dust Control Item no. 300 001DL

Forced Action Mixers	40
Motor, V	24
Output, kW	О.
RPM	30
Drum capacity, L	41
Mixing capacity, L	40
Height, cm	10
Width/Length, cm	60
Weight, kg	64

* Also available as Vario or Speedy model. OL 40 .75 0 \cap 03-121 0/60 4

68/80 98

117-127 72/95 2001* 400 2.2 30 220 200 128-138 89/104

175

